

**TTG PR 14 LT R134A
(COD. E2107S0000)**



Professional orizzontale cabinet for the storage of
refrigerated foods

Technical data

| | |
|--------------------------|--|
| Temperature | +3°C +8°C |
| Voltage and Frequency | 230 V~ 50 Hz |
| Gas | R134a |
| Net dimension | 600 x 661 x 842 mm (l x p x h) |
| Packed dimension | 690 x 690 x 965 mm (l x p x h) |
| Gross capacity | 150 l |
| Net capacity | 109,8 l |
| Gross weight | 56.00 Kg |
| Net weight | 47.00 Kg |
| Heat insulation | Rigid polyurethane foam "HCFC/CFC/HFC" free |
| External cabinet | White plasticised steel sheet |
| Cabinet back | Polypropylene cardboard sheet |
| Inner tank | White prepainted non-toxic steel sheet |
| Door frame - colour | White prepainted aluminium |
| Glass | Triple insulating crystal |
| Handle | Metal and white plastic |
| Control board cover | White plastic |
| Top insert | plastic - customised " FUME" " color |
| Top upper panel | White plasticised steel sheet |
| Compressor | 1/6 HP |
| absorbed power | 170 W |
| Power consumption (24h) | 2,72 kWh/24h |
| Annual consumption (AEC) | 992,80 kWh/year |
| Index (EEI) | 47,95 |
| Energy efficiency class | C |
| Condensator | Static condensation system |
| Evaporator | Roll bond (fan assisted) |
| Climatic class - EN 441 | 4 (30°C-55%UR) |
| Plug | European - Angular Plug |
| Thermometer/Thermostat | Electronic touch screen - s.a.v.e. control System |
| Defrosting | Automatic |
| Inner shelves | White plastified shelves - 2 removable + 1 in the bottom of the tank |
| Standard equipment | Lock - internal light (led) - feet |
| Optional | Wheels |
| Brand | MONDIAL ELITE |
| Producer brand | MONDIAL GROUP |

The manufacturer will reserve the right to make any modification without prior notice.

| |
|------------|
| Updated on |
| 30/09/2016 |

**TTG PR 14 LT R134A
(COD. E2107S0000)**



Professional orizzontale cabinet for the storage of
refrigerated foods

Image



| |
|--------------------------|
| Updated on 30/09/2016 |
|--------------------------|